

# PT-202F

## Air Hydraulic Blind Riveter

**POWERFUL**

**VERSATILE**

**DURABLE**

**HIGH PRODUCTION**

### PT-202F Specifications:

<b>Pulling Force:</b>	<b>3889 lbs at 90 psi</b>
<b>Stroke Max:</b>	<b>.750"</b>
<b>Weight</b>	<b>5.8 lbs.</b>
<b>Dimensions:</b>	<b>12 1/2"H x 9 3/4"L x 5 3/8"W</b>
<b>Body:</b>	<b>Cast Metal Housing</b>



**R**EACTING TO THE NEED FOR A HIGH PRODUCTION QUALITY BLIND RIVETER with ability to install both Pop type and industrial quality blind rivets, FSI is pleased to offer the **PT-202F** air hydraulic riveter. Coupling industrial quality pneudraulic components with a well established and user friendly blind rivet nose assembly, the PT-202F offers a perfect complement to our line of limited production, field maintenance and repair riveters.

Ergonomically balanced and weighing only 5.8 lbs. the rugged metal case will offer years of service in both high production and harsh field maintenance environments. Coming standard with a three (3) piece jaw system and two (2) popular rivet nosepieces, the PT-202F will permit the installation of a wide range of commercial/industrial blind rivets in all materials thru 1/4" (including Pop Type, Interlock®, Magna-lok® and Monobolts®). Servicing the riveter is also easily accomplished with a bleeder tool furnished with each riveter.

**P.O. Box 1372  
1206 E. MacArthur St.  
Sonoma, CA 95476  
1-800-344-2393  
(707) 935-1170  
FAX: (707) 935-1828  
CAGE Code: 64878  
www.fsirivet.com  
Email: sales@fsirivet.com**

**GSA** Contract #  
GS-06F-0009L

# PT-202F Capabilities

## Typical Fastener Types Installed

### CherryMax®/HuckMax®



### Magna-bulb®



### Magna-lok®



### POP® Rivet



With the appropriate nosepiece or adapter/nose assembly the PT-202F will install aerospace single action blind rivets such as MS20600 series (self plugging and pull thru rivet) NAS1400A (CherryLock "A"® / Olympic-lok®), NAS1900S/U (Huck SMLS), and MS90353/54/S/U (Huck and Cherry Blind Bolts) thru 3/16", as well as most all industrial quality blind rivets thru 1/4" diameter such as Mil-R-24243 (POP® rivets), M7885/10 (Huck Magnalok®, Cherry Monobolts® & Interlocks®), and Huck Magna-bulbs® or Avdel Hemlok® rivets commonly used on military ground vehicles and ground support equipment.

Because of its compatibility with all other FSI riveters, the standard adapters found in all fielded FSI tool kits, including the popular D-100-MIL-1 (NSN 5180-01-201-4978) and D-100-MIL-2 (NSN 5180-01-201-4979), may be used to permit a wide range of specialty right angle, offset and extended straight pulling heads to be added to the PT-202F to enable its use in limited access areas. Contact your local FSI representative or email our factory at [sales@fsirivet.com](mailto:sales@fsirivet.com) for your specific needs.

## Common Adapters Used

