

PT-747 Universal Air Hydraulic Blind FASTENING SYSTEMS Riveter for High Production Applications

POWERFUL

VERSATILE

PRODUCTIVE

LIGHTWEIGHT

The New PT-747 Riveter offers high production users proven, highly reliable, air hydraulic technology coupled with a universal pulling head found in all FSI blind riveting tool systems. In seconds you can change nosepieces to accommodate a wide range of fasteners including, but not limited to:

CherryMax® / Cherry-Max® SST / Huck Max® / Huck-Clinch® / AllMax®, Cherrylock® " A" Olympic-lok®, **Olympic** Bulb-lok®, Avdel® MBC, Huck SMLS, Huck and Cherry Blind Bolts (S / U Type) thru 5/32" diameter, CherryMax® AB, Cherry "SPR" Nutplate Rivets, Huck Magnalok®, Cherry Interlock®, Avdel / Cherry Monobolts®, MS20600 Self-Plugging Rivets, (MIL-R-24243) **POP®** Gesipa / Olympic Rivets, **Bulb-Tite Rivets, Avdel** AVEX® & Cherry Q Type Rivets.





Like all our tool systems you may add a number of adapters to enable use of special extended straight, offset, right angle and side ejection pulling heads, permitting use of most any limited access areas.

PT-747 Specifications:

Weight: 3.9 lbs. Noise Level: 71dB (A)

Vibration: less than 2.5 m/s²

Air Consumption: .09 SCF/Cycle (2.55 L/Cycle)

90 psi (6.2 bar) Min. / Air Pressure:

110 psi (7.6 bar) Max.

.437" Stroke:

Pulling Force: 2,100 lbs @ 90 psi **Cycle Time:** Approx. One Second

Construction: Rugged Cast Aluminum Body

Alloy Steel Pulling Head

P.O. Box 1372 1206 E. MacArthur St. Sonoma, CA 95476

> 1-800-344-2393 (707) 935-1170

FAX: (707) 935-1828

CAGE Code: 64878

www.fsirivet.com Email:

sales@fsirivet.com