



CLASS I DIVISION 2 SCREWDRIVERS

HAZLOC™
CLASS 1 DIVISION 2 RATED



"Quick Change"
1/4" Hex Shank Chuck

Torque Adjusting System

Auto-Stop
Fastening Function

L.E.D.
Indicator

Built-in L.E.D. Light

Anti-Slip
Dimpled Grip

Beeper Indicator

MAKSTAR®
CHARGING SYSTEM

2.0Ah
Nickel-Metal Hydride
12V
Ni-MH

Kit Includes:
2 Ea. (2.0Ah) Makstar®
Battery BH1220,
Makstar® Charger
DC18RA & Steel Case



CLASS I DIVISION 2 RATED

ADVANCED TECHNOLOGY



- UL listed for Class I Division 2 locations for maximum 50°C ambient
- Meets the NEC Article 513 Aircraft Hanger requirements for Class I Division 2 locations
- Tested to Mil Standard 810F, Method 511.4

SMART SYSTEM

AUTO BATTERY SHUT-OFF



- Shuts off the tool when battery capacity drops below 5%

Indication Lamp and Beeper

- Precision sensor indicates following conditions with light and/or beeping: sufficient fastening, insufficient fastening, low battery power, and battery too low to operate

REPETITIVE ACCURACY

TORQUE ACCURACY

- Torque accuracy of: +/- 10% with $C_m \geq 1.67$
- Automatically shuts-off tool when pre-set fastening torque is reached to ensure accuracy

PRECISE TORQUE CONTROL SCREWDRIVERS



BFH040FRAE



BFH040RAE



BFH090FRAE



BFH090RAE



BFH120FRAE

| | BFH040FRAE | BFH040RAE | BFH090FRAE | BFH090RAE | BFH120FRAE |
|--------------------------------------|----------------|----------------|------------------|------------------|--------------------|
| Voltage | 12V | 12V | 12V | 12V | 12V |
| Capacities | 1/4" Hex Shank | 1/4" Hex Shank | 1/4" Hex Shank | 1/4" Hex Shank | 1/4" Hex Shank |
| Max. Fastening Torque [Nm (in.lbs.)] | .8 - 4.5(7-40) | .8 - 4.5(7-40) | 3.4 - 9.0(30-80) | 3.4 - 9.0(30-80) | 5.0 - 12.0(44-106) |
| No Load Speed (RPM) | 400 | 400 | 400 | 400 | 400 |
| LED Lamp | YES | NO | YES | NO | YES |
| LED Pass/Fail | YES | YES | YES | YES | YES |
| Audible Signal | YES | NO | YES | NO | YES |
| Length | 7-15/32" | 7-15/32" | 7-15/32" | 7-15/32" | 7-15/32" |
| Height | 10-15/32" | 10-15/32" | 10-15/32" | 10-15/32" | 10-15/32" |
| Width | 2-13/16" | 2-13/16" | 2-13/16" | 2-13/16" | 2-13/16" |
| Weight | 3.3 lbs. | 3.3 lbs. | 3.3 lbs. | 3.3 lbs. | 3.3 lbs. |