

**Pistol Grip Sander**

**Model No. 5540**

- Aluminum housing
- Built-in speed regulator
- Free Speed: 14,000 rpm
- Weight: 2.2 lb. (1.0 kg)
- Length: 4.3" (109 mm)
- Air inlet size: 1/4" NPT
- Spindle thread: 7/16"-20
- Recommended hose size: 3/8" (10 mm)
- 3" (75 mm) and 4-1/2" (115 mm) backing pads included
- Air Consumption: 12.0 cfm (340 l/s) avg. – 30.0 cfm (847 l/s) max.



**5" (125 mm) Right Angle Air Sander**

**Model No. 5265**

- Lockoff lever throttle
- Safety lever throttle
- Removable auxiliary handle and wrenches
- Built-in speed regulator
- Rear exhaust
- Backing pad for 5" (125 mm) abrasives included
- Free Speed: 7000 rpm
- Weight: 2.9 lb. (1.32 kg)
- Length: 9.4" (240 mm)
- Spindle thread: 5/8" - 11
- Air inlet size: 1/4" NPT
- Recommended hose size: 3/8" (10 mm)
- Air Consumption: 4.5 cfm (127 l/s) avg. – 18.0 cfm (508 l/s) max.



**Right Angle Sander**

**Model No. 5287A**

- Lockoff lever throttle
- Support handle can be mounted on either side
- Rear exhaust
- Backing pad for 7" (180 mm) abrasives included
- Free Speed: 6000 rpm
- Pad diameter: 7" (180 mm)
- Weight: 4.4 lb. (2.0 kg)
- Length: 12.6" (320 mm)
- Air inlet size: 1/4" NPT
- Recommended hose size: 3/8" (10 mm)
- Spindle thread: 5/8"-11
- Air Consumption: 4.8 cfm (135 l/s) avg. – 19.2 cfm (542 l/s) max.

**G geared Random Orbital Sander**

**Model No. 5557**

- Geared output
- Built-in speed regulator
- Built-in hand guard
- Vinyl grip and head cover
- Free speed: 850 rpm
- Pad diameter: 8" (200 mm)
- Weight: 4.8 lb. (2.2 kg)
- Height: 4.7" (119 mm)
- Air inlet size: 1/4" NPT
- Recommended hose size: 3/8" (10 mm)
- 8" (200 mm) backing pad included
- Air Consumption: 5.0 cfm (142 l/s) avg. – 20.0 cfm (565 l/s) max.
- 3/16" (5 mm) Orbit Diameter



**Dual Action Sander**

**Model No. 5558A**

- Built-in speed regulator
- Dual action sanding
- Vinyl grip and head cover
- Free speed: 10,000 rpm
- Pad diameter: 6" (150 mm)
- Weight: 4.3 lb. (2.0 kg)
- Height: 5.4" (137 mm)
- Air inlet size: 1/4" NPT
- Recommended hose size: 3/8" (10 mm)
- Sound level: 79 dB(A)
- 6" (150 mm) backing pad included
- Air Consumption: 5.0 cfm (142 l/s) avg. – 10.0 cfm (282 l/s) max.
- 3/8" (10 mm) Orbit Diameter



**Dual Piston Inline Sander**

**Model No. 5560**

- Dual handles
- Positive lock paper clamps
- 2500 spm (strokes per minute)
- Paper size: 2-3/4" x 17-1/2" (70 x 445 mm)
- Weight: 6.8 lb. (3.1 kg)
- Height: 16" (406 mm)
- Air inlet size: 1/4" NPT
- Recommended hose size: 3/8" (10 mm)
- Air Consumption: 3.0 cfm (85 l/s) avg. – 12.0 cfm (340 l/s) max.



**SAFETY PRECAUTION:** Read and follow all safety and operating instructions.  
**WARNING:** Face & eye protection must be worn while operating power tools, per ANSI B186.1